



## EZ1017 Calcium Hardness Analyser

**Kat. číslo produktu:** EZ1017.XXXXXXXXXX  
**CZK Cena bez DPH:** Kontaktujte nás

### Online colorimetric analysis of Calcium Hardness in water

EZ1000 Calcium Hardness Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

### Flexibility that meets your needs

EZ Series Calcium Hardness Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### Technické údaje

Alarm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analogové výstupy:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Automatické čištění:	Ano
Certifikace:	CE compliant / ETL certified
Demineralised water:	For rinsing / dilution
Digitální výstupy:	Optional: Modbus (TCP/IP, RS485)
Doba cyklu :	10 min (dilution + 5 min.)

Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Hmotnost:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interference :	Dissolved Copper Cu(II) > 2 mg/L, Iron Fe(II) > 20 mg/L, Manganese > 10 mg/L, Zinc > 5 mg/L, Lead > 5 mg/L, Aluminium > 5 mg/L and Tin Sn(IV) interfere. Orthophosphate precipitates Calcium at the pH of the test. Strontium and Barium give a positive interference and alkalinity in excess of 300 mg/L may cause an indistinct end point in hard waters. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Jaký je obsah balení:	EZ1017 Calcium Hardness Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 3 x empty 2.5L Reagent Containers with Fittings (for Colour, Acid, and EDTA Solution) and 1 x empty 5L Reagent Container with Fittings (for Buffer)
Kalibrace:	Automatic, 2-point; frequency freely programmable
Materiál:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: galvanised steel, powder coated
Metoda:	Colorimetric
Metoda měření:	Colorimetric measurement at 610 nm using hydroxynaphthol blue/EDTA
Mez detekce:	≤ 2.5 µg/L CaCO <sub>3</sub>
Napájení:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Odtok:	Atmospheric pressure, vented, min. Ø 32 mm
Okolní teplota:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parametr:	Calcium Hardness
Počet proudů vzorku:	1, 2, 4, or 8
Požadavky na vzorek:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Přesnost:	Better than 2% full scale range for standard test solutions
Přístroj:	EZ1017
Průtoková rychlost:	100 - 300 mL/min
Reagent Requirements:	Keep between 10 - 30 °C
Rozměry (V x Š x H):	690 mm x 465 mm x 330 mm
Rozsah měření:	0.025 - 1 mg/L CaCO <sub>3</sub>
	Optional:
	0.005 - 0.25 mg/L
	0.005 - 0.5 mg/L
	0.2 - 4 mg/L (with internal dilution)
	0.4 - 8 mg/L (with internal dilution)
	0.25 - 10 mg/L (with internal dilution)
	0.625 - 25 mg/L (with internal dilution)
	1.25 - 50 mg/L (with internal dilution)
	1.875 - 75 mg/L (with internal dilution)
	2.5 - 100 mg/L (with internal dilution)
Teplota vzorku:	10 - 30 °C

Tlak vzorku:	By external overflow vessel
Třída ochrany:	Analyser cabinet: IP44 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Záruka:	24 měsíců

---

## **Jaký je obsah balení**

EZ1017 Calcium Hardness Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 3 x empty 2.5L Reagent Containers with Fittings (for Colour, Acid, and EDTA Solution) and 1 x empty 5L Reagent Container with Fittings (for Buffer)