



**Be Right™**



## EZ1022 Hydrogen Peroxide Analyser

Kat. číslo produktu:

**EZ1022.XXXXXXXX**

CZK Cena bez DPH:

Kontaktujte nás

### Online colorimetric analysis of Hydrogen Peroxide ( $H_2O_2$ ) in water

EZ1000 Hydrogen Peroxide Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low  $\mu\text{g/L}$  range.

#### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### Flexibility that meets your needs

EZ Series Hydrogen Peroxide Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

#### Technické údaje

|                      |   |
|----------------------|---|
| Alarm:               | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts |
| Analogové výstupy:   | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)                       |
| Automatické čištění: | Ano   |
| Certifikace:         | CE compliant / ETL certified  |
| Demineralised water: | For rinsing / dilution  |
| Digitální výstupy:   | Optional: Modbus (TCP/IP, RS485)  |
| Doba cyklu :         | 10 min (dilution + 5 min.)  |

|                       |  |
|-----------------------|--|
| Earth connection:     | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>  |
| Hmotnost:             | 25 kg  |
| Instrument air:       | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air   |
| Interference :        | Oxidants like Bromine, Bromamine, Chlorine, Copper Cu(II) > 8 mg/L, Chromate, Iodine, Iodoamines, Iron Fe(III) > 20 mg/L, Nitrite, Ozone and Manganese may oxidize the DPD colour solution. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar. |
| Jaký je obsah balení: | EZ1022 Hydrogen Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)   |
| Kalibrace:            | Automatic, 2-point; frequency freely programmable  |
| Materiál:             | Hinged part: Thermoform ABS, door: PMMA  |
|                       | Wall section: galvanised steel, powder coated  |
| Metoda měření:        | Colorimetric measurement at 510 nm using DPD   |
| Mez detekce:          | ≤ 2 µg/L   |
| Napájení:             | 100 - 240 VAC, 50/60 Hz  |
|                       | Max. power consumption: 120 VA   |
| Odtok:                | Atmospheric pressure, vented, min. Ø 32 mm   |
| Okolní teplota:       | 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)  |
| Parametr:             | Hydrogen Peroxide  |
| Počet proudů vzorku:  | 1, 2, 4, or 8  |
| Požadavky na vzorek:  | Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU  |
| Přesnost:             | Better than 2% full scale range for standard test solutions  |
| Přístroj:             | EZ1022   |
| Průtoková rychlosť:   | 100 - 300 mL/min   |
| Reagent Requirements: | Keep refrigerated.   |
| Rozměry (V x Š x H):  | 690 mm x 465 mm x 330 mm   |
| Rozsah měření:        | 5 - 500 µg/L H <sub>2</sub> O <sub>2</sub>   |
|                       | Optional:  |
|                       | 2 - 125 µg/L   |
|                       | 2 - 250 µg/L   |
|                       | 0.04 - 2.0 mg/L (with internal dilution)   |
|                       | 0.08 - 4.0 mg/L (with internal dilution)   |
|                       | 0.5 - 50 mg/L (with internal dilution)   |
| Teplota vzorku:       | 10 - 30 °C   |
| Tlak vzorku:          | By external overflow vessel  |
| Třída ochrany:        | Protection class: Analyser cabinet: IP44 / Panel PC: IP65  |
| Validation:           | Automatic; frequency freely programmable   |
| Záruka:               | 24 měsíců  |
| Zdroj napájení:       | 100 - 240 VAC, 50/60 Hz  |

## Jaký je obsah balení

EZ1022 Hydrogen Peroxide Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and 2 x empty 2.5L Glass Containers with Fittings (for Colour and Buffer Solution)