



**Be Right™**



## EZ1030 Phenol Analyser

**Kat. číslo produktu:**

**EZ1030.XXXXXXXX**

CZK Cena bez DPH:

Kontaktujte nás

### Online colorimetric analysis of Phenol in water

EZ1000 Phenol Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

### Flexibility that meets your needs

EZ Series Phenol Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### Technické údaje

|                      |   |
|----------------------|---|
| Alarm:               | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts               |
| Analogové výstupy:   | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)                                     |
| Automatické čištění: | Ano   |
| Certifikace:         | CE compliant / ETL certified  |
| Demineralised water: | For rinsing / dilution  |
| Digitální výstupy:   | Optional: Modbus (TCP/IP, RS485)  |
| Doba cyklu :         | 10 min (dilution + 5 min)   |
| Earth connection:    | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup> |

|                       |   |
|-----------------------|---|
| Hmotnost:             | 25 kg   |
| Instrument air:       | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air  |
| Interference :        | Oxidising agents such as Chlorine, Sulphur compounds like Sulphide. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.  |
| Jaký je obsah balení: | EZ1030 Phenol Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution) |
| Kalibrace:            | Automatic, 2-point; frequency freely programmable   |
| Materiál:             | Hinged part: Thermoform ABS, door: PMMA   |
|                       | Wall section: Galvanised steel, powder coated   |
| Metoda měření:        | Colorimetric measurement at 505 nm using 4-aminoantipyrine, conform with standard method APHA   |
| Mez detekce:          | $\leq 10 \mu\text{g/L}$   |
| Napájení:             | 100 - 240 VAC, 50/60 Hz   |
|                       | Max. power consumption: 120 VA  |
| Odtok:                | Atmospheric pressure, vented, min. Ø 32 mm  |
| Okolní teplota:       | 10 - 30 °C $\pm 4$ °C deviation at 5 - 95% relative humidity (non-condensing)   |
| Parametr:             | Phenol  |
| Počet proudů vzorku:  | 1, 2, 4, or 8   |
| Požadavky na vzorek:  | Maximum particle size 100 $\mu\text{m}$ , $< 0.1 \text{ g/L}$ ; Turbidity $< 50 \text{ NTU}$  |
| Přesnost:             | Better than 3% full scale range for standard test solutions   |
| Přístroj:             | EZ1030  |
| Průtoková rychlosť:   | 100 - 300 mL/min  |
| Reagent Requirements: | Keep between 10 - 30 °C   |
| Rozměry (V x Š x H):  | 690 mm x 465 mm x 330 mm  |
| Rozsah měření:        | 0.1 - 2 mg/L Phenol   |
|                       | Optional:   |
|                       | 0.01 - 0.25 mg/L  |
|                       | 0.025 - 0.5 mg/L  |
|                       | 0.025 - 1 mg/L  |
|                       | 0.8 - 8 mg/L (with internal dilution)   |
|                       | 1.6 - 16 mg/L (with internal dilution)  |
|                       | 2 - 200 mg/L (with internal dilution)   |
| Teplota vzorku:       | 10 - 30 °C  |
| Tlak vzorku:          | By external overflow vessel   |
| Třída ochrany:        | Protection class: Analyser cabinet: IP44 / Panel PC: IP65   |
| Validation:           | Automatic; frequency freely programmable  |
| Záruka:               | 24 měsíců   |
| Zdroj napájení:       | 100 - 240 VAC, 50/60 Hz   |

---

## Jaký je obsah balení

EZ1030 Phenol Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) and 1 x empty 2.5L Reagent Container with Fittings (for Colour Solution)