



Be Right™



## EZ6202 Total Copper Analyser, 1 stream, Modbus RS485

Kat. číslo produktu: EZ6202.990A1C02

CZK Cena: Kontaktujte nás

Datum dodání na vyžádání

### Trace metal analysis of Total Copper in water by online voltammetry

#### About the 6000 Series

The EZ6000 Series of Online Trace Metal Analysers are based on the technology of stripping voltammetry, a sensitive analytical technique that can be automated for the determination of trace levels of metals in water. For many metals the EZ6000 Series boasts limits of quantification in the low ppb range, comparing the technique favorably with AAS or ICP analysis.

#### Single, multiple and total parameter configurations

Several product sublines with a wealth of combinations are available for determination of trace metals, including the standard single parameter and multi-parameter configurations without digestion. Measurement of complexed or adsorbed metals is possible by means of the configurations with built-in digester. Combinations of metals depend on the choice of working electrode and the priority metals for your application.

#### Advanced features

The EZ6000 Series build upon tried and tested voltammetry technology used in many clean water applications, in an industrial mainframe with the following prime features:

- Excellent selectivity and sensitivity
- Built-in sample digestion unit (hot acid or UV)
- Smart automatic features
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Higher measuring ranges: internal sample dilution
- Multiple stream analysis

There are many additional options available. Please contact Hach for more details.

---

### Technické údaje

Alarm: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Certifikace:	CE compliant / UL certified
Chladící voda:	Flow rate approx. 5 L/h; temperature max. 30 °C; pressure max. 0.5 bar
Demineralised water:	For rinsing and/or dilution
Digitální výstupy:	Modbus RS485
Doba cyklu :	20 minutes (dilution + 5 min.)
Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Hmotnost:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interference :	Antimony (III), bismuth (III), organic matter may interfere. Fats, oil, proteins, surfactants and tar.
Kalibrace:	Automatic, 2-point; frequency freely programmable
Materiál:	Hinged part: Thermoform ABS, door: plexiglass
	Wall section: Galvanised steel, powder coated
Metoda měření:	Stripping voltammetry using carbon electrode
Mez detekce:	≤ 10 µg/L
Napájení:	220 - 240 VAC, 4 A, 50/60 Hz, max. power consumption 440 VA
Odtok:	Atmospheric pressure, vented, min. Ø 64 mm
Okolní teplota:	10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parametr:	Copper, total
Počet proudů vzorku:	1 stream
	Optional:
	1 to 6 streams
Požadavky na vzorek:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Přesnost:	Better than 5% full scale range for standard test solutions
Průtoková rychlost:	100 - 300 mL/min
Reagent Requirements:	Keep between 10 - 30 °C
Rozsah měření:	10 - 100 µg/L Cu
Teplota vzorku:	10 - 30 °C
Tlak vzorku:	By external overflow vessel
Třída ochrany:	Analyser cabinet: IP55 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Výstup:	Modbus RS485
	Optional:
	Active 4 - 20 mA max. 500 Ohm load, 1 to 8 outputs
	RS232, Modbus TCP/IP
Záruka:	2 roky