



Be Right™



EZ1011 Copper Cu(II) Analyser, 1 stream, Modbus RS485

Kat. číslo produktu: EZ1011.99001C02

CZK Cena: Kontaktujte nás

Datum dodání na vyžádání

Online colorimetric analysis of dissolved Copper in water

EZ1000 Copper Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low $\mu\text{g/L}$ range.

Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

Flexibility that meets your needs

EZ Series Copper Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

Technické údaje

Alarm:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Certifikace:	CE compliant / UL certified
Digitální výstupy:	Modbus RS485
Doba cyklu :	10 min (dilution + 5 min)
Earth connection:	Dry and clean earth pole with low impedance ($< 1 \text{ Ohm}$) using an earth cable of $> 2.5 \text{ mm}^2$
Hmotnost:	25 kg
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interference :	Acidity, metal ions like Aluminium (III) > 10 mg/L, Cyanide, Hardness, Iron (III) > 10 mg/L, Nickel (II) and Silver (II). Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibrace:	Automatic, 2-point; frequency freely programmable
Materiál:	Hinged part: Thermoform ABS, door: plexiglass
	Wall section: Galvanised steel, powder coated
Metoda měření:	Colorimetric measurement at 480 nm using bathocuproine method; conform respectively with USEPA Method 8506 and standard method APHA 3500-Cu (C)
Mez detekce:	≤ 10 µg/L
Napájení:	110 - 220 VAC, 2 A, 50/60Hz
	Max. power consumption: 150 VA
	Other voltages available on request
Odtok:	Atmospheric pressure, vented, min. Ø 64 mm
Okolní teplota:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Parametr:	Copper
Počet proudů vzorku:	1 stream
	Optional:
	1 to 8 streams
Požadavky na vzorek:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Přesnost:	Better than 2% full scale range for standard test solutions
Průtoková rychlost:	100 - 300 mL/min
Reagent Requirements:	Keep between 10 - 30 °C
Rozměry (V x Š x H):	690 mm x 465 mm x 330 mm
Rozsah měření:	0.05 - 5 mg/L Cu(II)
	Optional:
	0.01 - 0.5 mg/L
	0.02 - 1.25 mg/L
	0.02 - 2.5 mg/L
	0.4 - 20 mg/L (with internal dilution)
	0.8 - 40 mg/L (with internal dilution)
	5 - 500 mg/L (with internal dilution)
Teplota vzorku:	10 - 30 °C
Tlak vzorku:	By external overflow vessel
Třída ochrany:	Analyser cabinet: IP55 / Panel PC: IP65
Validation:	Automatic; frequency freely programmable
Výstup:	Modbus RS485
	Optional:
	Active 4 - 20 mA max. 500 Ohm load, 1 to 8 outputs

RS232, Modbus TCP/IP

Záruka:

2 roky